


# SWP-508

# Premier IP Phones for Executive Communication

- 2.8" color LCD display
- 8 SIP lines, electronic page turning
- Encrypted calls (OpenVPN/TLS/SRTP)
- HD audio with noise reduction
- Supports USB recording and WiFi
- Remote address book management
- Business-style design, elegant and practical

The SWP-508 is a next-generation, premium business IP phone crafted for executives and professionals who demand superior communication tools. Featuring an elegant design and a vibrant 2.8-inch color LCD screen, the SWP-508 delivers an exceptional user experience through intuitive operation, rapid responsiveness, and an extensive feature set. Designed to enhance both collaboration and individual productivity, it sets a new benchmark for business communications.





#### **Key Features and Benefits**

- Ultra-HD Audio: Supports Opus codec for crystal-clear, lifelike call quality.
- Dual 100M/1000M Ethernet Ports: PoE power supply and USB interface for seamless connectivity and flexibility.
- 2.8-inch Color LCD: High-resolution backlit display for clear and vibrant visuals.
- 8 SIP Accounts: Supports multi-line calls for enhanced communication efficiency.
- Programmable Keys: Paperless design for quick access to essential functions.
- Five-party Conferencing: Enables seamless team collaboration with multi-party calls.
- Security Features: Encrypted calls with OpenVPN, TLS, and SRTP for secure communication.
- LDAP Integration: Centralized address book management for easy contact synchronization.
- DSS Expansion Support: Speed dial and real-time user status monitoring for greater convenience.
- Flexible Setup: PoE power supply and optional 2.4G/5.8G Wi-Fi for easy workspace configuration.
- Advanced Noise Reduction: Ensures crystal-clear calls, reducing background noise for enhanced voice quality.

S	SWP-508 Series Models - Optional Configurations				
	Model	Network	PoE	DSS Expansion	Power Adapter
	SWP-508M	10/100M	√	√	Optional
	SWP-508G	10/100/1000M	$\checkmark$	$\checkmark$	Optional
	SWP-508W	10/100M & WiFi	$\checkmark$	$\checkmark$	$\checkmark$



#### **Physical Specification:**

## **Phone Functionality**

- Support for 8 simultaneous SIP lines for managing multiple calls
- Multi-language supported
- Caller ID display with both name and number.
- Customizable keys for DSS, BLF monitoring, hotline, and speed dial.
- Operate in handle, hands-free, or headset mode.
- Call hold, mute, blind transfer, inquiry transfer, DND, call forwarding, and call waiting.
- Features such as multicast, intercom, text messaging, keypad lock, emergency calls, direct IP calls, redial, callback, and auto-answer.
- Five-party conference support, line sharing, and dialing rules.
- Choice of 10 built-in ringtones, with the option to upload custom ringtones.
- Manual or automatic synchronization of network time.
- Action URLs and URIs for advanced integration.

#### **Audio Characteristics**

- HD handle and hands-free audio for high-fidelity sound.
- Broadband codecs: G.722, Opus.
- Narrowband codecs: G.711, G.723.1, G.729AB, G.726, iLBC.
- DTMF support: In-band, Out-of-band (RFC 2833), and SIP INFO.
- Full-duplex hands-free communication.
- Acoustic echo cancellation (AEC), voice activity detection (VAD), comfort noise generation (CNG), packet loss compensation (PLC), background noise detection (BNE), automatic gain control (AGC).
- Dynamic adaptive RTP jitter buffer (up to 300 ms).

#### Address Book

- Blacklist management.
- Supports XML/LDAP address book with smart contact search.
- Export/import contacts.
- Local storage for up to 1,000 contacts.
- Call history including dialed, received, missed, and forwarded calls (up to 1,200 records).

#### **IP PBX Features**

- BLF, voice message support.
- Anonymous call management, rejection, call park, and call pickup.
- Server-based recording functionality.

#### Configuration & Maintenance

- Web configuration and phone menu configuration for easy setup.
- Supports automatic deployment via FTP/TFTP/HTTP/HTTPS/SIP PnP/TR-069.
- BIN/CFG configuration options and contact configuration export/import.
- Network packet capture and diagnosis tools available.
- Options for custom or full factory restore.

#### Network

- Supports IPv4, IPv6, and both.
- Flexible IP address allocation via Static IP or DHCP.
- VLAN support and data link layer protocols: CDP/LLDP.
- SIP v1 (RFC2543) and v2 (RFC3261) support, with redundant server capabilities.
- ICE, STUN, UDP/TCP/TLS transmission, and SRTP encryption protocol support.
- Anti-attack SIP trust server and security features like HTTPS, TR-069, OpenVPN, IEEE802.1X, and encrypted configuration files.
- Optional Wi-Fi support (2.4G & 5G).
- QoS support: VLAN tagging (802.1p/Q), Layer 3/ToS/DSCP, RTCP-XR, and VQ-RTCPXR.

#### Phone Interface

- 1 x RJ-9 headset interface, 2 x RJ-45 10/100/1000M Ethernet ports, USB 2.0 interface, DC power interface.
- 8 SIP line keys with LED, 4 soft keys, 12 standard number keys, 6 function keys, 5 navigation keys, and volume adjustment keys.
- Desktop or wall-mounted installation options.

#### **Product Specifications**

- 2.8-inch color LCD (320x240).
- Desktop size: 187mm\*184mm\*147mm.
- Power consumption: 2~3W (PoE support, IEEE 802.3af/at).
- ◆ Operating conditions: Humidity: 10~95%, Temperature: -10~50°C (+14~122°F).

### Packaging Information

- Contents: SWP-508 IP phone, Ethernet cable, handle, base, quick start guide, power adapter (AC 100~240V, DC 5V/1000mA).
- Packing: 10 units per carton, gross weight: 9.5 kg, box size: 535 mm × 410 mm × 230 mm, color box size: 211 mm × 195 mm × 100

